



**Application:** All Years

## Stainless Steel Paint



### Tools Needed



Search: **Paint**

[www.mamotorworks.com](http://www.mamotorworks.com)

*The pigment in Performance Choice® STAINLESS STEEL BLAST is 100% type 316L stainless steel to provide maximum corrosion resistance. Can be used on metal and many other surfaces for protection against weather, sunlight, oil and water. Dries quickly to a satin sheen finish.*

### Directions For Use:

#### STEP 1.

Surface must be clean and dry before painting. For best results, use when can is between 70 and 90F.

#### STEP 2.

Shake can at least one minute before and occasionally during use.

#### STEP 3.

Spray surface with steady even strokes at a distance of 8 to 10 inches. Several light coats give a better finish than one heavy coat.

#### STEP 4.

If clogging develops, turn spray button 1/4 turn or remove and clean button slot. Do not stick objects into can opening.

#### STEP 5.

After painting, turn can upside down and spray for two seconds to clear spray button.

#### STEP 6.

Discard empty can in trash pick-up. DO NOT incinerate or compact.

### WARNING! CONTAINS TOLUOL

### DANGER! KEEP AWAY FROM CHILDREN

### Extremely Flammable

Do not spray near HEAT, SPARKS or OPEN FLAME. Vapors will accumulate easily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE – Extinguish all flames, pilot lights and heaters. TURN OFF stoves, electric tools and appliances and any other sources of ignition.

### Harmful

Avoid contact with eyes, prolonged or repeated contact with skin. In case of eye contact, immediately flush thoroughly with water and get medical attention.



Mamotorworks



@CorvettePassion



MidAmericaMotorworks



CorvettePassion

**2900 North Third Street, Effingham, IL 62401**

**800.500.1500 • Worldwide: 217.540.4200 • FAX: 217.540.4800**

**[www.mamotorworks.com](http://www.mamotorworks.com) • [generalmail@mamotorworks.com](mailto:generalmail@mamotorworks.com)**

©Mid America Motorworks, Inc. All rights reserved.



## **Description (cont.)**

### **Contents Under Pressure**

Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water, and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120F. Do not discard empty can in home garbage compactor.

### **Vapor Harmful**

Use with adequate ventilation. Avoid continuous breathing of vapors or spray mist. OPEN windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Can be absorbed through the skin.

**INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.**

### **Notice:**

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain damage and nervous system damage to arms and legs. Can be absorbed through skin causing blood, lung, liver and kidney defects.