



Application: all models

Part Includes

1 – Side Terminal Battery Mount

Side Terminal Battery Mount



Tools Needed



STEP 1.

Read CAUTION! before installing switch.

STEP 2.

Remove key from ignition and turn off lights and all accessories.

STEP 3.

Keep disconnect arm in "open" position until all connections are complete.

STEP 4.

Remove battery cable from the negative (-) battery terminal.

STEP 5

Clean battery post for a good electrical contact.

STEP 6.

Install disconnect on the (-) battery terminal and position as desired. **MAKE SURE THAT YOUR HOOD OR OTHER METAL OBJECTS WILL NOT CONTACT THE SWITCH.**

STEP 7.

Reattach battery cable to the side of the disconnect not attached to battery.



CAUTION!

Batteries produce explosive gases and can explode! Wear eye protection; keep sparks, flame, and cigarettes away from battery. Remember, batteries contain sulfuric acid. Wear safety glasses. In case of contact with skin, eyes, or clothing, flush immediately with large amounts of water and follow through with medical help. Do not use the switch while operating starter, as the battery load may become inductive as well as resistive, causing an explosion if battery gases are present. Battery disconnects are for the use only in well ventilated areas. THE USE OF THIS DISCONNECT IS TO CUT BATTERY POWER ON A VEHICLE- AFTER THE VEHICLES



2900 North Third Street, Effingham, IL 62401
800.500.1500 • Worldwide: 217.540.4200 • FAX: 217.540.4800
www.mamotorworks.com • generalmail@mamotorworks.com

©Mid America Motorworks, Inc. All rights reserved.