



Application: 1997-2004

636-060



Search: *Shift Boots*
www.mamotorworks.com

Part Includes

1 - Door Handle Cover Pair

Door Handle Cover



Tools Needed



PREPARATION:

Clean and dry each door grab handle. The handle covers will fit either side.

INSTALLATION:

STEP 1:

If installing below 75 degrees, covers may need to be warmed up. This can be done by laying them in the sun for a few minutes, or CAREFULLY with a hair dryer. If using a hair dryer blow on the back of the leather or vinyl.

STEP 2.

Hold with soft part of Velcro towards the top of the door panel. Then wrap the bottom of the door handle cover around the door handle, then wrap the top part of the cover down to meet the bottom part and lock together the Velcro strip. It may be necessary to adjust/tighten the cover so it fits snug on the handle. Covers may loosen up in a hot car, and may need to adjusted/tightened, again.

CLEANING:

Leather or Vinyl covers can be cleaned with mild soap and water. Marks, such as pencil or crayon can be removed with (Cig. Lighter fluid), on a rag. The residue of the lighter fluid will evaporate almost immediately, without harming the cover material.



Mamotorworks



@CorvettePassion



MidAmericaMotorworks



CorvettePassion

2900 North Third Street, Effingham, IL 62401

800.500.1500 • Worldwide: 217.540.4200 • FAX: 217.540.4800

www.mamotorworks.com • generalmail@mamotorworks.com

©Mid America Motorworks, Inc. All rights reserved.



000-000

Description (cont.)