



Application: 1990-2013

Part Includes

4 - Stainless Steel 10 - 32x1.5" screws

EZ Clutch Pedal Pad Extension



Tools Needed



Search: *Interior Trim, Door Panels, Sunvisors*
www.mamotorworks.com

A. NOTES ABOUT EZ CLUTCH PEDAL PAD EXTENSION

STEP 1.

Orient Back plate with open end up to match pedal curvature. Place behind clutch pedal and snap up onto clutch shaft. Requires some effort to snap in place.

STEP 2.

Install the 4 supplied Stainless Steel 10-32x1.5" screws into EZ-Clutch Pedal Extension.

STEP 3.

Hold EZ-Clutch Pedal Extension on to clutch pedal face and align back plate with screws.

STEP 4.

Using a Phillips screwdriver, snug all 4 screws into place. Screws should align easily with back plate threaded brass inserts.

STEP 5.

Tighten 1/2 to 3/4 turn, screws should be tight but avoid over tightening.

STEP 6.

EZ-Clutch Pedal Extension should be tight and ready for use.



Mamotorworks



@CorvettePassion



MidAmericaMotorworks



CorvettePassion

2900 North Third Street, Effingham, IL 62401
800.500.1500 • Worldwide: 217.540.4200 • FAX: 217.540.4800
www.mamotorworks.com • generalmail@mamotorworks.com
©Mid America Motorworks, Inc. All rights reserved.